

ML390FB DOT MATRIX PRINTER



❖❖❖ ML390FB ❖❖❖ 24-PIN DOT MATRIX PRINTER

A TRULY VERSATILE PRINTER FOR EFFORTLESS HANDLING OF MULTIPLE PAPER TYPES

The ML390FB 24-pin dot matrix printer is characterised by its straight, flat paper path - just as suitable for printing on awkward stationery as for everyday use. The flexibility and compactness of this printer makes it ideal for high profile environments such as reception areas, airline counters and travel centres. It is just however as useful in any typical office environment where high quality word and data processing is needed.

MAIN FEATURES OF THE ML390FB PRINTER

- ❖❖❖ 106 column flatbed dot matrix printer
- ❖❖❖ Durable 24-pin print head for sharp text
- ❖❖❖ Up to 270 characters per second print speed
- ❖❖❖ Multi-part paper-handling (original + 4 copies)
- ❖❖❖ Ideal for general business applications and reception areas
- ❖❖❖ Versatile handling of a variety of print media using flat paper path



OKI

ML390FB DOT MATRIX PRINTER

PRODUCT SPECIFICATION

		ML390FB
General	Number of pins	24
	No. of multi-part forms	5 (one original + 4 copies)
Speed & throughput	Utility (12cpi & 10cpi)	270cps; 225cps
	Letter quality (12cpi & 10cpi)	90cps; 75cps
	Fastest print speed (12cpi)	270cps
Font & print features	Carriage width (10cpi)	106 columns
	Max. in compressed mode	212 columns
	Character pitch	10/12/15/17.1/20 pitch & proportional
	Graphics resolution	Up to 240 x 360 dpi
	Typeface & Font	Courier, Roman, Swiss, Prestige, Gothic, Swiss Bold, Utility
	Typestyle	Emphasised, Enhanced, Double Width, Double Height, Italics, Outline, Shadow, Bold, Superscript, Subscript, Underline
Emulations & interfaces	Printer emulations	Epson LQ, IBM ProPrinter X24E/X24E AGM
	Standard interfaces	Centronics Parallel
	Optional interfaces	Centronics Parallel or Serial RS 232C
Paper-handling	Continuous paper	76–305mm
	Card stock weight	45–189gsm
	First printable line (from top of page)	0.5mm
	Standard	Autoload single sheet, Paper parking, Push tractors
	Optional	Single bin cut sheet feeder
Physical	Dimensions (HxWxD)	200 x 465 x 343mm
	Weight	12kg
	Memory	Standard 23KB buffer (reduced buffer)
	Noise level	58dB(A)/56dB(A) (quiet mode)
Power	Power requirements	230V AC
	Frequency	50/60Hz
Reliability	Print head life	200 million characters
	Ribbon life	2 million characters (re-inking cartridge)
Supplies life	MTBF	5,000 hours



Only use genuine Oki Original consumables to ensure the best quality and performance from your hardware. Non Oki Original products may damage your printer's performance and invalidate your warranty. Specifications subject to change without notice. All trademarks acknowledged.

Oki Network Solutions
for a Global Society

OKI EUROPE, PART OF OKI ELECTRIC

OKI EUROPE LTD,
CENTRAL HOUSE, BALFOUR ROAD,
HOUNSLOW, MIDDLESEX, TW3 1HY,
UNITED KINGDOM
TEL: +44 (0)20 8219 2190
FAX: +44 (0)20 8219 2199
WWW.OKIEUROPE.COM



As an ENERGY STAR Partner, Oki Europe Ltd has determined that this product meets the ENERGY STAR guidelines for energy efficiency

©2003 Oki Europe Ltd.