

# T2265/T2280

## High speed and rugged design for easy use and heavy-duty operation



T2265

At top speeds of 1,100 and 900 characters per second, the T2280 and T2265 keep pace with the bustling, no-nonsense world where printing is time sensitive and critical. These devices produce multi-part invoices, shipping documents or bar code labels at a rate of 40,000 and 50,000 pages per month.



T2280

The T2280 is optionally configured with three input tractors (two front, one rear) and the T2265 is expandable to two front input tractors. Both printers handle up to 7-part forms with a straight paper path resulting in jam-free operation.

### High Throughput

- T2280: 1,100 characters per second/600 pages per hour in draft mode; near letter quality printing at 370 characters per second
- T2265: 900 characters per second/540 pages per hour in draft mode; near letter quality printing at 300 characters per second

### Superior Forms Handling

- Straight paper path for reliable forms handling
- Up to 7-part forms with no skewing or jamming
- Automatically adjusts for different forms thickness
- Load up to three forms at once (T2280)
- Automatic quick-tear

### Ease of Use

- Long life, 20 million character ribbon for less operator interventions

### Excellent Connectivity

- Serial and parallel standard
- 10/100 Ethernet and Twinax/Coax optional

Consumables

Ink Jet Printers


Laser Printers

Line Matrix Printers

**Serial Matrix Printers**

## Features & Specifications

	<b>T2265</b>	<b>T2280</b>
	136 Column	136 Column
		<b>T2280-2T</b> 136 Column with front and rear tractors (no color version available)
<b>Printing Technology</b>	24-wire serial impact dot matrix	
<b>Print Speed</b>	15 cpi: Draft 900 cps NLQ 300 cps LQ 150 cps  12 cpi: Draft 720 cps NLQ 240 cps LQ 120 cps  10 cpi: Draft 650 cps NLQ 200 cps LQ 100 cps	15 cpi: Draft 1100 cps NLQ 370 cps LQ 185 cps  12 cpi: Draft 880 cps NLQ 295 cps LQ 145 cps  10 cpi: Draft 800 cps NLQ 245 cps LQ 120 cps
<b>Workload</b>	40,000 pages per month	50,000 pages per month
<b>Copies</b>	Original + 6 (7-part forms)	Front: Original + 6 (7-part forms) Back: Original + 4 (5-part forms)
<b>Throughput</b>	540 pages per hour (ECMA 132/6.91, draft)	600 pages per hour (ECMA 132/6.91 draft)
<b>Graphic Resolution (VxH)</b>	Up to 360 x 360 dpi	
<b>Character Density</b>	(Emulation dependent) 5, 6, 7.5, 8.6, 10,12,15,17.1, 20 cpi	
<b>Line Density</b>	2, 3, 4, 6, 8, 12 lpi	
<b>Fonts</b>	Draft, Copy Draft, Courier, Roman, Sans Serif, OCR A, OCR B, 15 Bar Codes & scaleable LCP fonts	
<b>Compatibility</b>	IBM® Proprinter XL24e, Epson® LQ-2550, Epson® LQ-2170 (ESC P/2), MTPL	
<b>Paper Handling</b>	Standard: Front insertion, Push tractor with paper parking and AGA.	Standard: Front insertion, Push tractor with paper parking and AGA T2280-2T: 2nd push tractor
	Options: Additional front push tractor, automatic dual-bin sheet feeder (190 sheets per bin), face down output, paper cutter	
<b>Consumables</b>	20 M Character Ribbon; Printhead Life: 500 M Characters (draft)	
<b>Noise Level</b>	53 dB(A) (ISO 7779)	
<b>MTBF</b>	10,000 hours @ 25% duty cycle	
<b>Environmental</b>	+10°C to +35°C (temperature); 16% to 73% (relative humidity)	
<b>Power Requirements</b>	AC 230V, 50/60Hz and 120V, 60Hz (selectable)	
<b>Power Consumption</b>	60 Watts	70 Watts
<b>Physical (WxDxH)</b>	24.5" x 16.9" x 10.9"; 42 lbs.	
<b>Interfaces</b>	Standard: Bi-directional Centronics Parallel and RS-232 Serial (auto-switching); 128K buffer  Optional: Ethernet (Novell & TCP/IP), Twinax, Coax, Twinax IPDS, Coax IPDS, RS-422, Current Loop	
<b>Options</b>	Twinax or Coax (with or without IPDS), Ethernet, Current Loop and RS-422 interfaces; second front push tractor, paper cutter, dual bin sheet feeder*, face down output*; printer stand, pedestal cabinet; color; and DEC® LA75	



T2280-2T with optional front push tractor



BSI ISO 9001: 1994  
Certificate No. FM  
28149



4500 Daly Drive, Suite 100  
Chantilly, VA 20151

T 800.436.4266  
www.tallygenicom.com

\*Automatic dual bin sheet feeder and face down output module not available for T2280-2T.