

Small yet highly productive

imageRUNNER
1133, 1133A and 1133iF

you can

This compact multifunctional series features double-sided document output as standard and optional Wi-Fi. Time and cost saving capabilities ensure you hit deadlines and save money too.

| |
|---|
| UP TO 33 PPM / CPM, A4 BLACK-AND-WHITE |
| UP TO 1,050 SHEET CAPACITY |
| NETWORK READY, PCL*, AND OPTIONAL PS AND WI-FI |
| 5-LINE USER INTERFACE |
| CLASS-LEADING ENERGY EFFICIENCY |
| EMBEDDED UNIFLOW AND E-MAINTENANCE CAPABILITY |



The image shown above is the imageRUNNER 1133



The image shown above is the imageRUNNER 1133iF

Productivity and efficiency.

- Fast print speeds up to 33ppm
- Up to 1050 sheet paper capacity
- 50 sheet Duplex Document feeder*
- Print and scan directly from USB memory key and Send in Colour to email and network folder*
- Simple, hassle-free integration - Network ready, optional WiFi, PCL and PS support*
- Compatibility with Canon's e-Maintenance service offers remote diagnostics, automated meter readings and consumables monitoring

* Available on selected models- please see specifications for full details

Environmental.

- Energy Star certified and low TEC rating
- Consumes as little as 2.5 watts in sleep mode
- Save paper - automatic double-sided output

Cost Control.

- Compatibility with uniFLOW solution offers Cost Centre selection and reporting for cost control and monitoring
- Accurate billing through e-Maintenance
- Enhanced productivity and class-leading energy efficiency maximises value

Security .

- Secure Print** keeps documents confidential during printing
- Department ID secures access to the device
- Canon's uniFLOW solution offers the flexibility and convenience of My Print Anywhere secure release

** RAM-based secure print for up to 5 jobs

ImageRUNNER

Canon

Specifications: imageRUNNER 1100 series

| | |
|---|---|
| imageRUNNER 1133 series Machine Type Available Core functions | Mono Laser Multifunctional. imageRUNNER 1133: Print, Copy, Scan imageRUNNER 1133A: Print, Copy, Scan imageRUNNER 1133IF: Print, Copy, Scan, Send and Fax |
| PRINTER SPECIFICATIONS Print speed Printing method Print Resolution Double sided printing Printing from memory media Paper input (Standard) | Up to 33 ppm (A4) Monochrome laser beam printing 600 x 600 dpi, Up to 1200 x 1200 dpi (Enhanced) Automatic Supported memory media: USB memory key Supported file types: JPEG, TIFF 500-sheet paper cassette 50-sheet multi-purpose tray 500-sheet cassette 1050 sheets |
| Paper input (Option) Maximum paper input capacity Paper output capacity Finishing capabilities Supported media types | 50-sheets (60-89gsm) Group Cassette and optional cassette: Multi-purpose tray: Plain paper, Recycled paper, Heavy paper, Bond Plain paper, Recycled paper, Heavy paper, Bond, Transparency, Label, Envelope |
| Supported media sizes | Cassette and optional cassette: Multi-purpose tray: A4, A5, B5, Legal, Letter, Executive A4, A5, B5, Legal, Letter, Executive, Statements, Envelope (COM10, Monarch, DL, ISO-C5, ISO-B5) Custom sizes Width 76 to 216 mm, Length 127 to 356 mm 60 to 128 g/m ² |
| Supported media weights | Cassette and optional cassette: Stack Bypass: UFR-II-LT(Standard) PCL5e/6 (Standard with IR1133IF, Option on IR1133A) PostScript Level 3 Emulation (Option for all models) PCL fonts: 93 Roman 136 Roman PS fonts: UFR-II-LT: Windows® 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7/ Server 2008 R2, MAC OS X (10.4.9 or later) Windows 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7/ Server 2008 R2, MAC OS X (10.4.9 or later) Windows 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7/ Server 2008 R2, MAC OS X (10.4.9 or later) MAC OS 9.1 or later, MAC OS X (10.2.8 or later) Windows 2000/ Server 2003/ Server 2008/ XP/ Vista/ 7 Please refer to http://software.canon-europe.com for availability of print solutions for other Operating Systems and environments including AS/400, UNIX, Linux and Citrix. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place |
| Printer Language(s) | PCL5e/6 (Standard with IR1133IF, Option on IR1133A) PostScript Level 3 Emulation (Option for all models) PCL fonts: 93 Roman 136 Roman PS fonts: UFR-II-LT: Windows® 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7/ Server 2008 R2, MAC OS X (10.4.9 or later) Windows 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7/ Server 2008 R2, MAC OS X (10.4.9 or later) Windows 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7/ Server 2008 R2, MAC OS X (10.4.9 or later) MAC OS 9.1 or later, MAC OS X (10.2.8 or later) Windows 2000/ Server 2003/ Server 2008/ XP/ Vista/ 7 Please refer to http://software.canon-europe.com for availability of print solutions for other Operating Systems and environments including AS/400, UNIX, Linux and Citrix. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place |
| Fonts | PCL fonts: 93 Roman 136 Roman PS fonts: UFR-II-LT: Windows® 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7/ Server 2008 R2, MAC OS X (10.4.9 or later) Windows 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7/ Server 2008 R2, MAC OS X (10.4.9 or later) Windows 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7/ Server 2008 R2, MAC OS X (10.4.9 or later) MAC OS 9.1 or later, MAC OS X (10.2.8 or later) Windows 2000/ Server 2003/ Server 2008/ XP/ Vista/ 7 Please refer to http://software.canon-europe.com for availability of print solutions for other Operating Systems and environments including AS/400, UNIX, Linux and Citrix. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place |
| Operating system compatibility | PCL: Windows 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7/ Server 2008 R2, MAC OS X (10.4.9 or later) Windows 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7/ Server 2008 R2, MAC OS X (10.4.9 or later) Windows 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7/ Server 2008 R2, MAC OS X (10.4.9 or later) MAC OS 9.1 or later, MAC OS X (10.2.8 or later) Windows 2000/ Server 2003/ Server 2008/ XP/ Vista/ 7 Please refer to http://software.canon-europe.com for availability of print solutions for other Operating Systems and environments including AS/400, UNIX, Linux and Citrix. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place |
| SEND SPECIFICATIONS Optional/Standard | Standard on IR1133IF. Not supported on IR1133A models Platen/DADF: up to 300 dpi in Black and White or Colour E-Mail/ PC(SMB, FTP) Max. 200 |
| Destinations Address Book / Speed dials File formats Universal Send Feature Sets | TIFF (B&W), JPEG, PDF, PDF (Compact) No |
| FAX SPECIFICATIONS Optional/Standard | Standard on IR1133IF. Not supported on IR1133A models Modem Speed Fax Resolution Super G.3 33.6kpbs (Up to 3 seconds/page!) Standard: 200 x 100 dpi Fine: 200 x 200 dpi Photo: 200 x 200 dpi Super fine: 200 x 400 dpi Ultra fine: 400 x 400 dpi |
| Fax Memory Speed Dials Group Dials/ Destinations Sequential Broadcast Memory backup Other features | Up to 512 pages ¹ Max. 200 (including 19 one-touch dials) Max. 199 dials/ Max 199 destinations Max. 201 locations 1 hour Fax Forwarding, Dual Access, Remote Reception, PC Fax (TX only) |
| GENERAL SPECIFICATIONS Warm-up Time Interface type | Approx. 11 seconds or less from power on USB 2.0 Hi-Speed 10BASE-T/100BASE-TX Optional Wireless 802.11b/g 1 x Host-USB interface (Front of device) Optional additional Host-USB interface for uniFLOW MiCARD reader (Right-side of device) TCP/IP (L2/L3 Port 9100, HTTP), SMB, SNMP v1, WSD, IPv4/ IPv6 support |
| Network protocols | TCP/IP (L2/L3 Port 9100, HTTP), SMB, SNMP v1, WSD, IPv4/ IPv6 support |
| Processor Speed Memory Hard Disk Drive | 300 Mhz 256 MB (shared) No (RAM-based Secure Print standard) |
| CONTROL PANEL Dimensions with trays (W x D x H) | 5-line monochrome backlit LCD display IR1133 (platen model): 450 x 472 x 413 mm / 450 x 472 x 550 mm (with optional cassette) IR1133A/IF (ADF models): 450 x 472 x 465 mm / 450 x 472 x 603 mm (with optional cassette) IR1133A/IF: 450 x 1,141 x 724 mm (with the optional paper cassette attached) IR1133: 450 x 1,044 x 721 mm (with the optional paper cassette attached) IR1133IF: Approx. 20.7 kg (21.5 kg with Starter Cartridge) IR1133A: Approx. 20.5 kg (21.3 kg with Starter Cartridge) IR1133: Approx. 18.3 kg (19.1 kg with Starter Cartridge) 220-240 V (±10%), 50/60 Hz (±2 Hz) Maximum: Approx. 1200 W Standby: Approx. 9 W Sleep Mode: Approx. 2.5 W Typical Electricity Consumption (TEC): 1.3 kWh on all models |
| Installation space (W x D x H) | IR1133A/IF: 450 x 1,141 x 724 mm (with the optional paper cassette attached) IR1133: 450 x 1,044 x 721 mm (with the optional paper cassette attached) IR1133IF: Approx. 20.7 kg (21.5 kg with Starter Cartridge) IR1133A: Approx. 20.5 kg (21.3 kg with Starter Cartridge) IR1133: Approx. 18.3 kg (19.1 kg with Starter Cartridge) 220-240 V (±10%), 50/60 Hz (±2 Hz) Maximum: Approx. 1200 W Standby: Approx. 9 W Sleep Mode: Approx. 2.5 W Typical Electricity Consumption (TEC): 1.3 kWh on all models |
| Weight | IR1133A/IF: 450 x 1,141 x 724 mm (with the optional paper cassette attached) IR1133: 450 x 1,044 x 721 mm (with the optional paper cassette attached) IR1133IF: Approx. 20.7 kg (21.5 kg with Starter Cartridge) IR1133A: Approx. 20.5 kg (21.3 kg with Starter Cartridge) IR1133: Approx. 18.3 kg (19.1 kg with Starter Cartridge) 220-240 V (±10%), 50/60 Hz (±2 Hz) Maximum: Approx. 1200 W Standby: Approx. 9 W Sleep Mode: Approx. 2.5 W Typical Electricity Consumption (TEC): 1.3 kWh on all models |
| Power Source Power Consumption | IR1133A/IF: 450 x 1,141 x 724 mm (with the optional paper cassette attached) IR1133: 450 x 1,044 x 721 mm (with the optional paper cassette attached) IR1133IF: Approx. 20.7 kg (21.5 kg with Starter Cartridge) IR1133A: Approx. 20.5 kg (21.3 kg with Starter Cartridge) IR1133: Approx. 18.3 kg (19.1 kg with Starter Cartridge) 220-240 V (±10%), 50/60 Hz (±2 Hz) Maximum: Approx. 1200 W Standby: Approx. 9 W Sleep Mode: Approx. 2.5 W Typical Electricity Consumption (TEC): 1.3 kWh on all models |
| Noise Levels | IR1133A/IF: 450 x 1,141 x 724 mm (with the optional paper cassette attached) IR1133: 450 x 1,044 x 721 mm (with the optional paper cassette attached) IR1133IF: Approx. 20.7 kg (21.5 kg with Starter Cartridge) IR1133A: Approx. 20.5 kg (21.3 kg with Starter Cartridge) IR1133: Approx. 18.3 kg (19.1 kg with Starter Cartridge) 220-240 V (±10%), 50/60 Hz (±2 Hz) Maximum: Approx. 1200 W Standby: Approx. 9 W Sleep Mode: Approx. 2.5 W Typical Electricity Consumption (TEC): 1.3 kWh on all models |
| Software and printer management | IR1133A/IF: 450 x 1,141 x 724 mm (with the optional paper cassette attached) IR1133: 450 x 1,044 x 721 mm (with the optional paper cassette attached) IR1133IF: Approx. 20.7 kg (21.5 kg with Starter Cartridge) IR1133A: Approx. 20.5 kg (21.3 kg with Starter Cartridge) IR1133: Approx. 18.3 kg (19.1 kg with Starter Cartridge) 220-240 V (±10%), 50/60 Hz (±2 Hz) Maximum: Approx. 1200 W Standby: Approx. 9 W Sleep Mode: Approx. 2.5 W Typical Electricity Consumption (TEC): 1.3 kWh on all models |
| Security Features | IR1133A/IF: 450 x 1,141 x 724 mm (with the optional paper cassette attached) IR1133: 450 x 1,044 x 721 mm (with the optional paper cassette attached) IR1133IF: Approx. 20.7 kg (21.5 kg with Starter Cartridge) IR1133A: Approx. 20.5 kg (21.3 kg with Starter Cartridge) IR1133: Approx. 18.3 kg (19.1 kg with Starter Cartridge) 220-240 V (±10%), 50/60 Hz (±2 Hz) Maximum: Approx. 1200 W Standby: Approx. 9 W Sleep Mode: Approx. 2.5 W Typical Electricity Consumption (TEC): 1.3 kWh on all models |
| CONSUMABLES Toner Cartridge/s | IR1133A/IF: 450 x 1,141 x 724 mm (with the optional paper cassette attached) IR1133: 450 x 1,044 x 721 mm (with the optional paper cassette attached) IR1133IF: Approx. 20.7 kg (21.5 kg with Starter Cartridge) IR1133A: Approx. 20.5 kg (21.3 kg with Starter Cartridge) IR1133: Approx. 18.3 kg (19.1 kg with Starter Cartridge) 220-240 V (±10%), 50/60 Hz (±2 Hz) Maximum: Approx. 1200 W Standby: Approx. 9 W Sleep Mode: Approx. 2.5 W Typical Electricity Consumption (TEC): 1.3 kWh on all models |
| SPECIFICATIONS FOR OPTIONS Cassette Feeding Unit | IR1133A/IF: 450 x 1,141 x 724 mm (with the optional paper cassette attached) IR1133: 450 x 1,044 x 721 mm (with the optional paper cassette attached) IR1133IF: Approx. 20.7 kg (21.5 kg with Starter Cartridge) IR1133A: Approx. 20.5 kg (21.3 kg with Starter Cartridge) IR1133: Approx. 18.3 kg (19.1 kg with Starter Cartridge) 220-240 V (±10%), 50/60 Hz (±2 Hz) Maximum: Approx. 1200 W Standby: Approx. 9 W Sleep Mode: Approx. 2.5 W Typical Electricity Consumption (TEC): 1.3 kWh on all models |
| ADDITIONAL OPTIONS Additional Options | IR1133A/IF: 450 x 1,141 x 724 mm (with the optional paper cassette attached) IR1133: 450 x 1,044 x 721 mm (with the optional paper cassette attached) IR1133IF: Approx. 20.7 kg (21.5 kg with Starter Cartridge) IR1133A: Approx. 20.5 kg (21.3 kg with Starter Cartridge) IR1133: Approx. 18.3 kg (19.1 kg with Starter Cartridge) 220-240 V (±10%), 50/60 Hz (±2 Hz) Maximum: Approx. 1200 W Standby: Approx. 9 W Sleep Mode: Approx. 2.5 W Typical Electricity Consumption (TEC): 1.3 kWh on all models |
| FOOTNOTES [1] Based on ITU-T Standard Chart No. 1 [2] Declared noise emission in accordance with ISO 7779 [3] Based on 6% coverage | IR1133A/IF: 450 x 1,141 x 724 mm (with the optional paper cassette attached) IR1133: 450 x 1,044 x 721 mm (with the optional paper cassette attached) IR1133IF: Approx. 20.7 kg (21.5 kg with Starter Cartridge) IR1133A: Approx. 20.5 kg (21.3 kg with Starter Cartridge) IR1133: Approx. 18.3 kg (19.1 kg with Starter Cartridge) 220-240 V (±10%), 50/60 Hz (±2 Hz) Maximum: Approx. 1200 W Standby: Approx. 9 W Sleep Mode: Approx. 2.5 W Typical Electricity Consumption (TEC): 1.3 kWh on all models |
| Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ® All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. | IR1133A/IF: 450 x 1,141 x 724 mm (with the optional paper cassette attached) IR1133: 450 x 1,044 x 721 mm (with the optional paper cassette attached) IR1133IF: Approx. 20.7 kg (21.5 kg with Starter Cartridge) IR1133A: Approx. 20.5 kg (21.3 kg with Starter Cartridge) IR1133: Approx. 18.3 kg (19.1 kg with Starter Cartridge) 220-240 V (±10%), 50/60 Hz (±2 Hz) Maximum: Approx. 1200 W Standby: Approx. 9 W Sleep Mode: Approx. 2.5 W Typical Electricity Consumption (TEC): 1.3 kWh on all models |
| Microsoft, Windows and Windows Vista is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries. | IR1133A/IF: 450 x 1,141 x 724 mm (with the optional paper cassette attached) IR1133: 450 x 1,044 x 721 mm (with the optional paper cassette attached) IR1133IF: Approx. 20.7 kg (21.5 kg with Starter Cartridge) IR1133A: Approx. 20.5 kg (21.3 kg with Starter Cartridge) IR1133: Approx. 18.3 kg (19.1 kg with Starter Cartridge) 220-240 V (±10%), 50/60 Hz (±2 Hz) Maximum: Approx. 1200 W Standby: Approx. 9 W Sleep Mode: Approx. 2.5 W Typical Electricity Consumption (TEC): 1.3 kWh on all models |



Canon Copiers
3 The Forum
Tring Technology Park
Icknield Way
Tring
Hertfordshire HP23 4JX

www.canoncopiers.co.uk
Tel: 08000 822226
Fax: 01442 828811
Email: info@canoncopiers.co.uk

