

Professional, convenient
All-In-One colour solution
for small businesses

i-SENSYS
MF9220Cdn

you can



Impress with colour. Give your business a big advantage with Canon's professional output. This robust, colour laser all in one offers powerful SEND functionality and duplex efficiency in an easy to use and compact unit.

21 PPM
COLOUR PRINTING
AND COPYING

EASY OPERATION
WITH INTUITIVE
USER INTERFACE

ENERGY EFFICIENT

POWERFUL
SEND FUNCTION
MAKES SHARING
DOCUMENTS EASY

FULL INPUT AND
OUTPUT DUPLEX
CAPABILITIES

LARGE PAPER
CAPACITY FOR
REDUCED
DOWN-TIME

LDAP SUPPORT

Key features

- Colour laser All-In-One
- 21 ppm colour printing and copying
- High quality professional colour output
- Quick First-Print & energy efficient
- Network ready
- Scan to email, network folder & USB memory key
- 3.5 inch (8.8cm) colour TFT display with Easy-Scroll Wheel
- Double-sided print/copy/scan/fax
- 50-sheet Duplex ADF
- 850 maximum paper capacity
- Energy efficient

What's in the Box

Main unit, Cartridge 711 C/M/Y/K, Power cord, USB cable, Starter guide manual on CD, User software CD, Warranty card

Dimensions (WxDxH)

546 mm x 527 mm x 632 mm

Supported OS

Windows 7 / Server 2008 R2/ Server 2008/ Server 2003/ XP/ Vista/ 2000

Mac OS X version 10.4.9-10.6.X (Web distribution only)

Linux (Web distribution only)



PRINT



COPY



FAX



SCAN

Canon

Specifications



- 1 Flatbed & DADF
- 2 Intuitive user interface
- 3 Standard 250 sheet cassette
- 4 Cartridge 711:
4 cartridges available:
Black, Cyan, Magenta and Yellow

MF9220Cdn	
Machine type	Colour Laser All-In-One
Available functions	Print, Copy, Scan and Fax
PRINTER	
Print speed	Up to 21 ppm colour and mono (A4)
Printing method	Colour laser beam printing
Print quality	Up to 2400 x 600 dpi with Automatic Image Refinement
Print resolution	600 x 600 dpi
Double sided printing	Automatic
Printer languages	UFRII-LT
Print margins	5 mm-top, bottom, left and right
Toner saver mode	Yes
COPIER	
Copy speed	Up to 21 cpm colour and mono (A4)
First Copy Output Time (FCOT)	Approx. 12.5 seconds or less
Copy resolution	Up to 600 x 600 dpi
Copy modes	Text/Photo/Map (Default), Printed Image, Photo, Text
Double sided copying	2-sided to 2-sided (Automatic)
Multiple copy	Up to 99 copies
Reduction / Enlargement	50-200% in 1% increments
Toner saver mode	Yes
Other features	Frame Erase, Collate, 2 on 1, 4 on 1
SEND FUNCTIONS	
Scan to file server	FTP, SMB
Scan to E-mail and i-Fax	SMTP, POP3, i-Fax (Simple mode)
Scan to USB memory key	Yes
File formats	TIFF, JPEG, PDF, PDF (Compact)
SCANNER	
Type	Colour
Scan resolution	Optical: Up to 600 x 600 dpi
Colour scanning depth	24 bit/24 bit (input/output)
Greyscales	256 levels
Compatibility	TWAIN ¹ , WIA ¹
Max. scan width	216 mm
FAX	
Modem speed	Super G3 33.6kbps (Up to 3 seconds/page ²)
Receive mode	Fax only, Fax/Tel Auto Switch, Answer Mode, Manual RX
Fax resolution	200 x 100 dpi: 8 pels/mm x 3.85 lines/mm 200 x 200 dpi: 8 pels/mm x 7.7 lines/mm 200 x 400 dpi: 8 pels/mm x 15.4 lines/mm 400 x 400 dpi: 16 pels/mm x 15.4 lines/mm
FAX memory	Up to 1,000 pages ²
Speed dials	Max. 200 dials
Group dials/destinations	Max. 199 dials / Max. 199 destinations
Sequential broadcast	Max. 232 locations
Memory backup	1 hour
Double sided faxing	Yes (Transmit and Receive)
Other features	Fax Forwarding, Dual Access, Remote Reception, PC Fax (TX only)
MEDIA HANDLING	
Scanner type	Flatbed and Duplex Automatic Document Feeder (DADF)
Paper input (Standard)	250-sheet cassette 100-sheet multi-purpose tray 50-sheet DADF
Paper input (Option)	500-sheet cassette
Paper output	250-sheet
Media types	Plain paper, Recycled paper, Heavy paper, Transparency, Label, Envelope
Media sizes	Cassette and optional pedestal: A4, A5, B5, Legal, Letter, Executive Multi-purpose tray: A4, A5, B5, Legal, Letter, Executive, Statement, Envelope (COM10, Monarch, DL, ISO-C5, ISO-B5) Custom sizes: Width 76.2 to 215.9 mm; Length 127.0 to 355.6 mm. DADF: One-sided scanning: A4, A5, B5, Legal, Letter, Custom sizes (W x L): Max 215.9 mm x 355.6 mm Min. 128 mm x 139.7 mm) Two-sided scanning: A4, Legal, Letter
Media weights	Cassette and optional pedestal: 60 to 120 g/m ² Multi-purpose tray: 60 to 176 g/m ² DADF: One-sided scanning: 50 to 105 g/m ² , Two-sided scanning: 64 to 105 g/m ²

INTERFACE & SOFTWARE	
Interface type	USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX, 2 x USB memory slot
Operating System compatibility	Windows 7 / Server 2008 R2/ Server 2008/ Server 2003/ XP/ Vista/ 2000 Mac OS X version 10.4.9-10.6.x ^{3,5} Linux ^{4,5}
Software and printer management	NetSpot Device Installer, Remote User Interface (RUI), Department ID Management
GENERAL FEATURES	
Duty cycle	Max. 65,000 pages per month
Warm-up Time	Approx. 60 seconds from power on
Memory	384 MB (shared)
Control panel	3.5 inch (8.8cm) colour TFT display with Easy Scroll-Wheel
Dimensions with trays (W x D x H)	546 mm x 527 mm x 632 mm
Installation space (W x D x H)	546 mm x 1140 mm x 792 mm 546 mm x 1140 mm x 1095 mm (with optional Cassette Feeding Unit-AC1 attached)
Weight	Approx. 43.3 kg
Operating environment	Temperature: 10 to 32°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation)
Power Source	220-240V (±10%) 50/60Hz (±2Hz)
Power Consumption	Maximum: Approx. 1210 W Active: Approx. 470 W Standby: Approx. 35 W Sleep mode: Approx. 1.2 W ⁶ Typical Electricity Consumption (TEC): 2.3 kWh/week
Noise Levels	Sound Pressure ⁷ : Active: 66 dB(A) or less Standby: 43 dB(A) or less
CONSUMABLES	
Cartridges	Cartridge 711 Black (6,000 pages ⁸) Cartridge 711 Cyan (6,000 pages ⁸) Cartridge 711 Magenta (6,000 pages ⁸) Cartridge 711 Yellow (6,000 pages ⁸)
ACCESSORIES/ OPTIONS	
Items	CST.FEEDING UNIT-AC1 (500 sheet cassette) HANDSET-J1 (Telephone handset)

All specifications subject to change without notice

[1] Scan to computer via USB connection is not supported

[2] Based on ITU-T Standard Chart No. 1

[3] Mac OS X support printing and PC faxing only

[4] Linux supports printing only

[5] Web distribution only

[6] Lowest possible power consumption in sleep mode. If the device is connected to a network with other computers that are switched ON, the power consumption will be approximately 17 W

[7] Declared noise emission in accordance with ISO 9296

[8] Based on 5% coverage



Canon Inc.
canon.com
Canon Europe
canon-europe.com

English Edition
© Canon Europa N.V., 2010

Canon

Professional, convenient
All-In-One colour solution
for small businesses

i-SENSYS
MF9220Cdn

you can



4 cartridges available:
Black, Cyan, Magenta and Yellow



For small, dynamic teams that
demand professional output
from an intelligent device

Sales Start Date: **February 2011**

The whole range consists of:

i-SENSYS MF9280Cdn, i-SENSYS MF9220Cdn,
i-SENSYS MF8350Cdn, i-SENSYS MF8330Cdn,
i-SENSYS MF8050Cn, i-SENSYS MF8030Cn

Box Dimensions (WxDxH)

649 x 720 x 892 mm

Box Weight

59 Kg (Gross)

Packet Style

Pallet

Quantity of item

1

MERCURY CODES

PRODUCT

Name	Mercury Code	EAN Code
i-SENSYS MF9220Cdn	-	-

OPTIONS

Consumables	Mercury Code	EAN Code
Cartridge 711 Yellow	1657B002AA	4960999403717
Cartridge 711 Magenta	1658B002AA	4960999403748
Cartridge 711 Cyan	1659B002AA	4960999403779
Cartridge 711 Black	1660B002AA	4960999403809
Accessories	Mercury Code	EAN Code
Cassette Feeding Unit-AC1	2339B002AA	4960999613819
Handset	Mercury Code	EAN code
HANDSET-J1 EUR	2821B003AA	4960999575698
HANDSET-J1 UK	2821B004AA	4960999575704
HANDSET-J1 SA	2821B005AA	4960999575711



PRINT



COPY



FAX



SCAN

Canon